

Webster Hardness Tester



Video



Contact us

Mikrosize Precision Instrument Co.,Ltd

A-4035 RuiFeng Business Expo, Wuhu City, China , 241000.

Web: www.mikrosize.com

Email: mikrosize@mikrosize.com



Features and Applications

Product Features

- Lightweight and Portable: With its small size and light weight (only 0.5KG), it is easy to carry and suitable for on-site testing;
- Easy to Operate: Place the sample between the anvil and indenter, press down the handle to read the value, and there are minimal requirements for operators;
- Non-destructive Testing: The testing process does not damage the workpiece, allowing direct testing of finished or semi-finished products;
- Measurement Range and Accuracy: The measurement range is 0-20HW with an accuracy of 0.5HW, meeting the hardness measurement needs of various materials;



Product Applications

- Widely used in the aluminum alloy industry for inspecting heat treatment effects, assisting in determining material composition, and monitoring production processes;
- In the copper alloy industry, it is used for material classification and screening, as well as processing technology optimization;
- Applied in the steel industry for quality inspection, performance research, and other fields such as scientific research, small component testing, and on-site testing services.



Instrument Appearance



1.Frame

2.Support Screw

3.Lower Handle



4.Adjusting Screw

5.Gauge Head

6.Indenter Cylinder


7.Anvil

Product Details




- Suitable for materials with two parallel surfaces, such as tubing, plate materials, and profiles;
- Easy to operate—just one clamp is needed, and the hardness value can be directly read out, allowing users to conveniently view operational details;
- No sampling required, and minimal operational skill is needed, enabling quick and convenient testing; During testing, place the specimen between the anvil and indenter, press down the handle until it feels fully compressed, and then directly read the hardness value from the gauge head;


The indenters of different models of the Webster hardness tester vary:



iWeb-20



iWeb-B75/iWeb-BB75



iWeb-B92

Technical Specification

Accuracy	$\leq \pm 1H$
Resolution	0.1H
Measuring Mode	AVE, MAX, Timing

Model	Applicable Materials	Hardness Range
iWeb-20	Aluminum Alloy	25~110 HRE 58~131 HV
iWeb-20a		
iWeb-20b		
iWeb-B75	Hard or Semi-hard Brass, Ultra-hard Aluminum Alloy	63~105 HRE
iWeb-B75b		
iWeb-BB75	Soft Naval Brass, Red Brass (Copper)	18~100 HRE
iWeb-BB75b		
iWeb-B92	Cold-rolled Steel Plate, Stainless Steel	50~92 HRB

Standard Delivery

Name	Qty	Photo
Main Unit	1 pc	
Hardness Block	1 pc	
Spare Indenter	1 pc	
Calibration Wrench	1 pc	
Small Screwdriver	1 pc	
Instrument Case	1 pc	

Optional Delivery

Optional	Spare indentor
	Standard Wiebull hardness block
	Dial cover glass

Mikrosize Precision Instrument Co.,Ltd

Add: A-4035 RuiFeng Business Expo , Wuhu City, China , 241000.

Tel: 0553-2836939 Fax:0553-2836938 Web: www.mikrosize.com

