

Mikrosize®

MBrin-3000SA

Semi-Automatic Brinell Hardness Tester



Video



Contact us

Mikrosize Precision Instrument Co.,Ltd

A-4035 RuiFeng Business Expo, Wuhu City, China , 241000.

Web: www.mikrosize.com

Email: mikrosize@mikrosize.com



Web: www.mikrosize.com

Email: mikrosize@mikrosize.com

Features and Applications

Product Features


- Closed loop loading, ready to use upon startup
- 12.1-inch touch screen, user-friendly and easy to operate
- Cmos directly captures indentation images
- Equipped with 11 test forces and 15 brinell hardness test scales for arbitrary selection
- Automatic turret simultaneously holds 3 sets of ball indenters, all capable of automatic participation in testing
- Two objective lenses and indenters are installed on the same turret, and both can participate in indentation diameter measurement.
- Based on the selected scale, the objective lens and indenter are automatically switched
- Pre-set dwell time and adjustable measurement indentation light source intensity functions
- Loading time displayed in real-time
- Display measured indentation length, hardness value, number of measurements, etc
- Test results can be converted between various hardness scales.
- Hardness test results can be printed and output
- Equipped with multiple communication interfaces: USB, RS232, wlan, RJ45LAN




Product Application

- During mechanical processing, the brinell hardness tester can be used to detect the hardness of raw materials to select suitable processing techniques and tools
Can be used to detect the hardness of mechanical parts
- (such as gears, bearings, bolts, etc.) To ensure they meet design requirements and performance standards
Can be used to detect the hardness of forgings to judge the effectiveness of the forging process and the quality of the forgings

Product Details




- 1. Display Screen
- 2. Automatic Turret
- 3. Indenter
- 4. Objective Lens
- 5. Test Anvil
- 6. Lifting Screw
- 7. Handwheel
- 8. Emergency Stop Button




- 1. Power Switch
- 2. USB Interface
- 3. Start Key
- 4. Power Cord Interface
- 5. RS232 Interface
- 6. RJ45LAN Interface

Product Details




This equipment uses closed loop loading. It is ready to use immediately after startup. Combined with high-precision sensors and a measurement system, it ensures accurate measurement results.




The automatic turret of this device is simultaneously equipped with 3 indenters of different sizes and 2 objective lenses of different magnifications. All can directly participate in measurement and observation. Based on the test scale selected by the user, the indenter and objective lens are automatically switched.

Product Functions




- | | | |
|---|---|---------------------------------|
| 1.Connect Device | 10.Dwell Time | 19.Automatic Measurement |
| 2.Open Image | 11.Test Results | 20.Camera Settings |
| 3.Save Image | 12.Hardness Fine Adjustment Key | 21.Camera Connection |
| 4.Crosshair Reset | 13.Brightness Adjustment | |
| 5.Crosshair | 14.Load Key | |
| 6.Zoom In Key | 15.Area Automatic Measurement | |
| 7.Zoom Out Key | 16.Three-Point Circle Manual Measurement | |
| 8.Test Scale | 17.Two-Point Circle Manual Measurement | |
| 9.Indenter/Objective Lens Switch | 18.Manual Measurement | |

Operation Interface



Scale Selection


3 Sizes of indenters combined with different test forces provide 15 test scales to choose from
 HBW2.5/31.25、HBW2.5/62.5、HBW2.5/187.5、HBW5/31.25、HBW5/62.5、HBW5/125、
 HBW5/250、HBW5/750、HBW10/100、HBW10/125、HBW10/250、HBW10/500、
 HBW10/1000、HBW10/1500、HBW10/3000



Scale Conversion


Can be converted to commonly used Rockwell and Vickers hardness scales
 HRA、HRB、HRC、HRD、HS、HV、HB、HR15N、HR30N、HR45NT

Operation Interface



Turret Selection



A 5-position automatic turret is simultaneously equipped with 3 sizes of indenters and 2 types of objective lenses. Click the corresponding indenter or objective lens based on the different test scale, and the turret automatically rotates to the corresponding position



Lifting Screw Control

Controls the raising, lowering, and stopping of the Lifting Screw. The lifting speed can be selected


Operation Interface



Camera Settings


Users can further improve image quality by adjusting detailed camera parameters such as gain and exposure.

Operation Interface



Data Statistics


The device records test data information, including indentation size, hardness value, converted hardness value, and indentation images.



Curve Graph

Recorded data is used by the device to generate curve graphs, making test results more intuitive and clear.

Operation Interface



Calibration


Calibrate using a standard hardness block. Note: Calibrate the objective lens currently in use, otherwise the calibration is invalid.



Settings


- Device com port selection
- Select conversion scale
- Set upper and lower limits
- Set elevating column speed
- Select display language

Operation Interface



Report Settings

Select the content of the output report, which can include indentation images and data statistical curve graphs.



Language Selection

Supports display in chinese and english. other languages can be customized.

Technical Specification

Name	Semi-Automatic Brinell Hardness Tester
Model	MBrin-3000SA
Test Range	8~650HBW
Test Force	31.25kg、62.5kg、100kg、125kg、187.5kg、250kg、500kg、750kg、1000kg、1500kg、3000kg 306.45N、612.9N、980.7N、1226N、1839N、2452N、4903N、7355N、9807N、14710N、29420N
Test Scales	HBW2.5/31.25、HBW2.5/62.5、HBW2.5/187.5、HBW5/31.25、HBW5/62.5、HBW5/125、HBW5/250、HBW5/750、HBW10/100、HBW10/125、HBW10/250、HBW10/500、HBW10/1000、HBW10/1500、HBW10/3000
Scale Conversion	HRA、HRB、HRC、HRD、HS、HV、HB、HR15N、HR30N、HR45N
Measurement Range	8~650HBW
Loading Method	Automatic Loading, Dwell, Unloading
Test Height (mm)	280mm
Test Throat (mm)	200mm
Main Test Force Loading Time	5~8s
Dwell Time	0~99s
Turret	Automatic
Objective Magnification	1X、2X
Camera Magnification	20X
Total Magnification	20X、40X
Indenter Diameter (mm)	Φ2.5、Φ5、Φ10
Indentation Repeatability	±0.8%
Data Display	12.1-inch industrial-grade touch screen
Data Output	Word , Excel or Printer
Illumination	LED
Communication Interfaces	USB、RJ45LAN、WLAN、RS232
Dimensions (LxWxH) mm	1000*595*350
Power Supply	AC220V/110V±5%, 50~60Hz
Net Weight	210KG

Standard Delivery

Name	Qty	Photo
Machine Mainframe	1	
Φ2.5mm Brinell Indenter	1	
Φ5mm Brinell Indenter	1	
Φ10mm Brinell Indenter	1	
Φ2.5mm, Φ5mm, Φ10mm Carbide Balls	3	
Φ230mm Platform	1	
60*90mm V-Anvil	1	
Hardness Block (150~250) HBW10/3000	1	
Hardness Block (80~110) HBW10/1000	1	
Test Block (150~250) HBW10/3000	1	
USB Software	1	
Dongle	1	
Anti-Dust Cover	1	
Allen Wrench	1	
Power Cord	1	
Fuse	2	
Product Certificate	1	
Instruction Manual	1	



Optional Delivery

Optional Accessories

Carbide balls

Various Work Stages

Various Hardness Blocks

Machine Internal Accessories

Various Indenters